

PowerLite[®]
1725
Multimedia Projector




Step up to brilliant wireless performance.

- Lightweight and travel friendly — weighs under 4.0 lb
- Ultra bright — 3000 lumens color and 3000 lumens white light output
- Incredible clarity and detail — native XGA (1024 x 768) resolution
- Rich, vibrant color — 3-chip optical engine
- Reliable performance — 3LCD technology
- Plug 'n Play — USB connection projects video and plays audio from a PC
- Easy wireless setup with USB connection key — just plug the key into the PC and then project
- Added flexibility — Windows Vista[®] Network Projector compatible
- Impressive presentations, without a computer — convenient USB memory device connectivity



PowerLite 1725

Multimedia Projector



ORDERING INFORMATION

Product Name	Product Code	UPC
PowerLite 1725	V11H268020	010343 86953 0
Replacement Lamp	V13H010L48	010343 86956 1
Replacement Air Filter	V13H134A19	010343 86957 8

SPECIFICATIONS

Projection System

Epson 3LCD, 3-chip optical engine

Projection Method

Front/rear/ceiling mode

Driving Method

Epson Poly-silicon TFT Active Matrix

Pixel Number

786,432 dots x 3 (1024 x 760) LCDs

White Light Output**

3000 lumens (ISO 21118 Standard)

Color Light Output**

3000 lumens

Aspect Ratio

4:3 (supports 16:9)

Native Resolution

1024 x 768 (XGA)

Resize

640 x 480 (VGA), 800 x 600 (SVGA), 1280 x 800 (WXGA), 1280 x 1024 (SXGA), 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1680 x 1050 (WSXGA+), 1600 x 1200 (UXGA)

Lamp Type

E-TORL™ 170 W UHE

Lamp Life*

Up to 4000 hours (Low Light Output Mode)
Up to 3000 hours (High Light Output Mode)

Throw Ratio Range

1.09 – 1.34

Size (projected distance)

30" – 300" (2.1' – 27.1')

Keystone Correction Automatic

Automatic: Vertical: ± 30 degrees
Manual: Vertical: ± 30 degrees

Contrast Ratio

Up to 2000:1

Color Reproduction

16.77 million colors

Plug 'n Play

Projector is Mac compatible via DVI to VGA adapter (not included)

PROJECTION LENS

Type

Manual focus/(optical) zoom

F-number

1.58 – 1.68

Focal Length

16.1 – 19.3 mm

Zoom Ratio

Optical zoom 1.0 – 1.2

OTHER

Display Performance

NTSC: 560 line
PAL: 560 line
(depends on observation of the multi-burst pattern)

Input Signal

NTSC/NTSC4.43/PAL/M-PAL/N-PAL/
PAL60/SECAM SDTV/HDTV

Interfaces

Computer/component video:

Mini D-sub HD 15 pin x 1

S-video: Mini DIN x 1

Composite video: RCA x 1

Audio in: Mini stereo x 1 in or out user

selectable

Variable audio out: Mini stereo x 1 in or

out user selectable

USB connector: Type B x 1 (USB display

with audio and mouse/keyboard control)

Type A x 1 (for USB memory device)

Wireless LAN module: 802.11 a/b/g

Audio Output

1 W mono speaker

Audio Signal

500 mV rms/47K ohm

Operating Temperature

41 ° to 95 °F (5 ° to 35 °C)

Power Supply Voltage

100 – 240 V ± 10%, 50/60 Hz AC

Power Consumption

Network on: 243 W, 9 W standby

Network off: 4 W standby

Fan Noise

High Light Output Mode: 39 dB

Low Light Output Mode: 30 dB

Security

Kensington-style lock provision

DIMENSIONS (W x D x H)

Including feet: 11.2" x 7.9" x 2.8"

Excluding feet: 11.2" x 7.9" x 2.6"

Weight: 3.96 lb/1.8 kg

REMOTE CONTROL

Features

Power, source search selection, computer, S-video, video, EasyMP, A/V mute, freeze, user ID, auto, aspect, color mode, num, page up and down, E-zoom, volume, help, menu, enter, esc and pointer functions

Operating Angle

Right/left:

Front: ± 60 degrees

Rear: ± 30 degrees

Upper/lower:

Front: -30 to +45 degrees,

Rear: ± 30 degrees

Operating Distance

19.7 ft (6 m)

SUPPORT — THE EPSON CONNECTION™

Pre-sales support

U.S. and Canada 800-463-7766

Internet website www.epson.com

Service Programs

Two-year limited warranty, Epson Road

Service program, Epson PrivateLine®

dedicated toll-free support (U.S. and

Canada only) and 90-day lamp warranty

Contents

Wireless LAN module, Quick Wireless Connection USB key, power cable, computer cable (VGA), audio adapter, projector remote control with batteries, USB cable, soft carrying case, user manual CD, EasyMP software CD, Quick Setup Sheet, PrivateLine support card, registration card, password protection sticker and security screw

ACCESSORY PART NUMBERS

Distribution amplifier ELPDA01
Image presentation camera (ELPDC05)
V12H162020

Replacement Quick Wireless Connection
USB key V12H005M04
Wired LAN module V12H005M0B

Replacement wireless LAN
module V12H306P11

Component to VGA video cable ELPKC19
S-video cable ELPV01
SwissGear® backpack ELPKS63
Wheeled soft case ELPKS62

Soft shoulder case for
projector and laptop
Molded hardshell case ELPKS58
50" portable screen ELPSC06

60" portable pop-up screen ELPSC07
80" portable pop-up screen ELPSC08
Duet™ screen ELPSC80

Epson DC-10s document camera ELPDC10S
Kensington security lock ELPSL01
Universal ceiling mount ELPMBPJF

PACKAGING SPECIFICATIONS

PowerLite 1725

Dimensions 19.4" x 14.2" x 7.6" (W x D x H)

Weight 10.56 lb

Replacement Lamp

Dimensions 5.1" x 5.5" x 5.6" (W x D x H)

Weight 0.24 lb

Master Carton

Dimensions 11.5" x 26.0" x 6.8" (W x D x H)

Weight 3.96 lb

Units Per Master Carton 10

Replacement Air Filter

Dimensions 3.5" x 4.8" x 1.9" (W x D x H)

Weight 0.08 lb

Master Carton

Dimensions 7.3" x 10.1" x 5.7" (W x D x H)

Weight 1.3 lb

Units Per Master Carton 10

* Lamp life results will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time.

** Light output varies depending upon color and brightness modes selected.

Epson America, Inc.

3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.

3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5